

Fiber Bragg Grating Sensor

Technica SA

Key Features

- High tensile strength
- EMI immunity
- Explosion proof
- Small size & weight
- Absolute Measurement
- Requires no calibration
- Cascaded capability
- Good performance cost ratio



Applications

- Civil engineering SHM (bridges, tunnels, buildings)
- Oil & Gas (platform SHM)
- Transportation (railway, roadways)
- Energy (wind turbines, pipelines, nuclear reactors)

Easy to use

Our fiber Bragg grating (FBG) technology which is recognized as the most promising and successful optical fiber sensing technology. Installation is easy as FBG sensors is mounted using conventional techniques and is designed for use a single of in series as part of a FBG array of sensors

Specifications

Parameter	Unit	Specifications	Remark
Wavelength	nm	1512 to 1588	Other wavelength available upon request
Wavelength Tolerance	nm	+/- 0.5	+/- 0.25 (optional)
Reflectivity	%	1 to 99	-
Reflection FWHM	nm	0.1 to 1	-
FBG Length	mm	1 to 20	-
Sidelop suppression ratio	dB	Min. 15	-
Fiber Type	-	SMF-28, Polyimide coated fiber, PM fiber	-
Recoat	-	Acrylate, polyimide	-
Pull Strength	kpsi	Min. 100	150, 200 kpsi (optional)
Optical Connector	-	FC/APC,FC/UPC	Others available upon request

MOI Beijing Representative

Address: Room 210, Xianfeng Building No.7 Shangdi
Kaituo Road, Haidian District, Beijing, China

Zip: 100085

Telephone: 86-10-62962540/62962541

Fax: 86-10-62962543

Email: info@micronoptics.com.cn

Website: www.micronoptics.com.cn



Micron Optics, Inc.
1852 Century Pl, NE
Atlanta, GA 30345
ph: 404/325-0005
fax: 404/325-4082
www.micronoptics.com